



STORAGE BATTERY SYSTEMS, INC.

Wall-Mount Nema Configuration Bypass Panels

Make-before-break; Kirk-Key, Shunt Trip, Aux Contacts, SKRU. 35kAIC standard Free-standing floor mount kits are available

when input voltage to UPS is different from output, consult with SBS engineering services

kVA	Voltage		Amperage "AF"	Round-Up "AT"	Breaker Quan	kAIC	Height Inches	Width Inches	Depth Inches	Weight LBS.
	Input	Output								
30	208	208	150	104	2	65	74.2	31	14	382
	208	208	150	104	3	65	74.2	31	14	389
	480	480	100	45	2	35	74.2	31	14	382
	480	480	100	45	3	35	74.2	31	14	389
40	208	208	150	139	2	65	74.2	31	14	382
	208	208	150	139	3	65	74.2	31	14	389
	480	480	100	60	2	35	74.2	31	14	382
	480	480	100	60	3	35	74.2	31	14	389
50	208	208	250	173	2	65	74.2	31	14	382
	208	208	250	173	3	65	74.2	31	14	389
	480	480	150	75	2	35	74.2	31	14	382
	480	480	150	75	3	35	74.2	31	14	389
65	208	208	250	226	2	65	74.2	31	14	382
	208	208	250	226	3	65	74.2	31	14	389
	480	480	150	98	2	35	74.2	31	14	382
	480	480	150	98	3	35	74.2	31	14	389
80	208	208	400	278	2	65	82.4	40	14	560
	208	208	400	278	3	65	82.4	40	14	569
	480	480	150	120	2	35	74.2	31	14	382
	480	480	150	120	3	35	74.2	31	14	389
100	208	208	400	347	2	65	82.4	40	14	560
	208	208	400	347	3	65	82.4	40	14	569
	480	480	150	150	2	35	74.2	31	14	382
	480	480	150	150	3	35	74.2	31	14	389
130	208	208	600	451	2	65	90.7	40	14	597
	208	208	600	451	3	65	90.7	40	14	604
	480	480	250	195	2	35	74.2	31	14	382
	480	480	250	195	3	35	74.2	31	14	389
160	208	208	600	555	2	65	90.7	40	14	597
	208	208	600	555	3	65	90.7	40	14	604
	480	480	250	241	2	35	74.2	31	14	382
	480	480	250	241	3	35	74.2	31	14	389
225	208	208	800	781	2	65	90.7	40	14	597
	208	208	800	781	3	65	90.7	40	14	604
	480	480	400	338	2	35	82.4	40	14	560
	480	480	400	338	3	35	82.4	40	14	569
300	480	480	600	451	2	35	90.7	40	14	597
	480	480	600	451	3	35	90.7	40	14	604
400	480	480	600	601	2	35	90.7	40	14	597
	480	480	600	601	3	35	90.7	40	14	604
500	480	480	800	752	2	65	90.7	40	14	608
	480	480	800	752	3	65	90.7	40	14	619
625	480	480	1200	940	2	65	90.7	40	14	608
	480	480	1200	940	3	65	90.7	40	14	619
750	480	480	1200	1128	2	65	90.7	40	14	608
	480	480	1200	1128	3	65	90.7	40	14	619

Most Common Configurations "AF" Frame Size- Trip Setting is Less

Custom configurations are available as are increased kAIC ratings. Please call Engineering Services at 800-554-2243 xt 3009 or email sbs@sbsbattery.com



Critical Power Solutions & Services Since 1915