



AC SERIES

Dependable, Durable and Powerful Access & Cleaning Batteries

With over 80 years of experience, Trojan Battery – the most trusted name in deep cycle technology – offers the **NEW AC Series** designed specifically to meet the needs of Floor Machine and AWP/Access applications.

Trojan's AC Series provides a broad range of dependable flooded/wet batteries in 6-volt and 12-volt sizes and delivers numerous features and benefits over competitor batteries, including:

- **Maxguard[®] Advanced Design Separator and Alpha Plus[®] paste formulation** for long life, industry leading performance and lower overall maintenance costs
- **Two battery case options – Polyon[™] case for exceptional durability in heavy service applications or generic case design for standard applications**
- **Increased product portfolio, with high to low capacity points to meet your application and economic needs, all with the same Trojan Quality**

With Trojan AC Series you can expect maximum uptime and more productive hours on the job with the benefits of selecting the right features and price you need.

We offer outstanding technical support provided by full-time application engineers.
Trojan batteries are available worldwide through Trojan's Master Distributor Network.


Call 800-423-6569 or 562-236-3000 for more information or visit us at www.trojanbattery.com.

AC SERIES

BCI GROUP SIZE	TYPE	CAPACITY ^A Minutes		CAPACITY ^B Amp-Hours (AH)		TERMINAL TYPE (See Back Cover)	DIMENSIONS ^C Inches (mm)			WEIGHT lbs. (kg)
		@25 Amps	@75 Amps	5 Hr Rate	20 Hr Rate		L	W	H ^D	
6 VOLT DEEP CYCLE BATTERIES										
902	J305E-AC	645	160	250	305	5	12 1/4 (311)	7 (178)	14 3/8 (365)	83 (38)
902	J305G-AC	678	175	258	315	5	12 1/4 (311)	7 (178)	14 3/8 (365)	88 (40)
902	J305P-AC*	711	195	271	330	6	11 5/8 (295)	7 (178)	14 3/8 (365)	96 (44)
902	J305H-AC*	781	215	295	360	6	11 5/8 (295)	7 (178)	14 3/8 (365)	98 (45)
903	L16E-AC	766	185	303	370	5	12 1/4 (311)	7 (178)	17 (432)	100 (46)
903	L16G-AC	789	200	320	390	5	12 1/4 (311)	7 (178)	17 (432)	107 (49)
903	L16P-AC*	850	220	344	420	6	11 5/8 (295)	7 (178)	16 3/4 (424)	114 (52)
903	L16H-AC*	935	245	357	435	6	11 5/8 (295)	7 (178)	16 3/4 (424)	125 (57)
12 VOLT DEEP CYCLE BATTERIES										
921	J185E-AC	312	82	144	175	5	15 1/2 (394)	7 (178)	14 5/8 (371)	102 (46)
921	J185G-AC	324	93	152	185	5	15 1/2 (394)	7 (178)	14 5/8 (371)	106 (48)
921	J185P-AC*	380	104	168	205	6	15 (381)	7 (178)	14 5/8 (371)	114 (52)
921	J185H-AC*	440	121	185	225	6	15 (381)	7 (178)	14 5/8 (371)	128 (58)

- A. The number of minutes a battery can deliver when discharged at a constant rate at 80°F (27°C) and maintain a voltage above 1.75 V/cell. Capacities are based on peak performance.
- B. The amount of amp-hours (AH) a battery can deliver when discharged at a constant rate at 80°F (27°C) for the 20 Hr rate and 86°F (30°C) for the 5-Hr rate and maintain a voltage above 1.75 V/cell. Capacities are based on peak performance.
- C. Dimensions are based on maximum size. Dimensions may vary depending on type of handle or terminal.
- D. Dimensions taken from bottom of the battery to the highest point on the battery. Heights may vary depending on type of terminal.

TERMINAL CONFIGURATIONS



Universal Terminal

Automotive Post & Stud Terminal

* Polyon™ Case



STORAGE BATTERY SYSTEMS, INC.

800-554-2243

www.sbsbattery.com