



S-12330



Specifications

Nominal Voltage		12V
Rated Capacity(20 hour rate)		33AH
Dimension	Total Height (with terminals)	180mm(7.09inches)
	Height	155mm(6.10inches)
	Length	196mm(7.72inches)
	Width	131mm(5.16inches)
Weight		Approx. 11.0kg(24.25lbs)


Discharge characteristics 77°F (25°C)



Characteristics

Capacity 77°F (25°C)	20 hour rate (1.65A)	33AH
	10 hour rate (3.07A)	30.7AH
	5 hour rate (5.62A)	28.1AH
	1 hour rate (19.8A)	19.8AH
	15 min rate (57.76A)	14.44AH
Internal Resistance	Full charged Battery 77°F (25°C)	9mΩ
Capacity affected by Temperature (20 hour rate)	104°F (40°C)	102%
	77°F (25°C)	100%
	32°F (0°C)	85%
	5°F (-15°C)	65%
Self-Discharge 77°F(25°C)	Capacity after 3 month storage	91%
	Capacity after 6 month storage	82%
	Capacity after 12 month storage	64%
Max. Discharge Current 77°F(25°C)	495A (5S)	
Terminal	Standard	F5
	Optional	F15
Charging (Constant Voltage)	Cycle	Initial Charging Current 6.6A Or Small 14.5V~14.9V/77°F (25°C)
	Float	13.6V~13.8V/77°F (25°C)

Duration of discharge vs. Discharge current



Constant Power discharge Watts Per Cell 77°F (25°C)

Cut off voltage V/cell	5M	10M	15M	30M	45M	1H	2H	3H	5H	8H	10H	12H	24H
1.60V	259	175	140	82.1	61.4	50.7	29.3	20.6	13.8	8.76	7.16	6.22	3.18
1.65V	256	174	138	81.9	61.0	50.0	28.9	20.3	13.8	8.76	7.16	6.22	3.18
1.67V	253	173	137	81.0	60.1	49.6	28.6	20.2	13.8	8.76	7.16	6.22	3.18
1.70V	248	171	135	78.8	58.9	48.8	28.2	19.9	13.8	8.76	7.16	6.22	3.18
1.75V	242	166	130	77.4	57.8	47.9	27.7	19.6	13.6	8.66	7.12	6.22	3.18
1.80V	235	161	126	76.1	56.7	47.1	27.2	19.4	13.4	8.54	7.05	6.18	3.18

Note The above data are average values, and can be obtained within 3 charge/discharge cycles. These are not minimum values.